

# ENVIROPEEL MA SERIES MOBILE APPLICATION UNITS

The outstanding cost-saving benefits from using Enviropeel protection are well documented. These mobile application units make savings even easier to achieve.

Enviropeel equipment is designed and manufactured in the US to meet industry requirements for easy to use, cost-effective infrastructure protection. Two standard units are available - the MA-5 and the MA-25. Both are highly mobile and site-ready with their own heating tank, pump, integrated control system and heated application hose.

The MA-5 is a lightweight small project and training unit whereas the MA-25 has the capacity for the most demanding projects with flexible power requirements, a built-in compressor and super-fast melt times from its patented recirculating heating tank.

Zone-2 versions of the MA-25, equipped with gas detection and explosion-proof electrics, are also available for use in hazardous areas such as offshore or in gas plants.

Proven in the most challenging environments, Enviropeel



MA Application Units deliver outstanding corrosion and ingress protection for bearings and flanges on site or within any type of facility. Call us for more information on how Enviropeel will reduce costs and increase your productivity.

## KEY BENEFITS

**Designed & manufactured in the US**

**Efficient, mobile and built to last**

**Easy to use electronic controls**

**Two sizes to match your requirements**

**Hose lengths from 8 - 60 ft**





# MA Unit Specifications

## Electrical Specifications

Machine Voltage: 120 VAC / 1 phase / 50-60 Hz

Total machine amperage: 15 Amps

## Size and Weight

Height: 30" x Width: x 20" x Depth: 26"

Weight: 100 lbs (45kg)

## Capacity

Tank Capacity: 7 lbs (3.2kg)

Melt Rate: 5 lbs (2.2kg) per hour

Std Hose length: 8 ft

## MA-5



## Electrical Specifications

Machine Voltage: 120/240 VAC / 1 phase / 50-60 Hz

Total machine amperage: 30 Amps

## Size and Weight

Height: 40" x Width: 20" x Depth: 37"

Weight: 395 lbs (180kg)

## Capacity

Tank Capacity: 55 lbs (25kg)

Melt Rate: 24 lbs (11kg) per hour

Std Hose length: 30 ft

## MA-25



*Technical information, equipment details and safety data sheets are available on our website, where there is much more information on the Enviropeel range of advanced reliability systems.*

*Contact us for advice and availability in your area*

### Enviropeel USA

3619 South Arlington Avenue, Indianapolis, IN 46203, USA  
1-317-631-9100 · [info@enviropeelusa.com](mailto:info@enviropeelusa.com)



[www.enviropeel.com](http://www.enviropeel.com)

**ENVIROPEEL**