

# SAFETY DATA SHEET ALOCIT 28.15 STANDARD GREY RAL7004

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name ALOCIT 28.15 STANDARD GREY RAL7004

Product number AS29498D

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses COLOURING OF EPOXIDE COMPOUNDS & SYSTEMS

## 1.3. Details of the supplier of the safety data sheet

Supplier ALOCIT USA

1128 South West Street, Indianapolis, Indiana 46225.

+1 317 631-9100

ALOCIT INTERNATIONAL

3 Charles Wood Road, Dereham, UK NR19 1SX

+44 1362 694915

## 1.4. Emergency telephone number

Emergency telephone 24 HR EMERGENCY TELEPHONE NUMBER: US +1 800 535 5053 UK + 44 (0) 7930 595916

#### SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Muta. 2 - H341

**Environmental hazards** Aquatic Chronic 2 - H411

**Human health** The liquid is irritating to eyes and skin.

Environmental The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

## 2.2. Label elements

#### Hazard pictograms







Warning

Signal word

Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

#### **ALOCIT 28.15 STANDARD GREY RAL7004**

#### Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

## Supplemental label information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Contains

bis-[4-(2,3-epoxipropoxi)phenyl]propane, 2,3-EPOXYPROPYL O-TOLYL ETHER, Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700, oxirane,

mono[(C12-14-alkyloxy)methyl] derivs., FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE

## 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current UK criteria.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### reaction product: bisphenol-A-(epichlorhydrin)

30-60%

CAS number: 25068-38-6 EC number: 500-033-5

## Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

BARIUM SULPHATE 30-60%

## Classification

Not Classified

## **ALOCIT 28.15 STANDARD GREY RAL7004**

TITANIUM DIOXIDE 10-30%

Classification
Not Classified

#### 2,3-EPOXYPROPYL O-TOLYL ETHER

5-10%

CAS number: 2210-79-9 EC number: 218-645-3

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Muta. 2 - H341

Aquatic Chronic 2 - H411

## bis-[4-(2,3-epoxipropoxi)phenyl]propane

<1%

CAS number: 1675-54-3 EC number: 216-823-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

## Formaldehyde, polymer with (chloromethyl)oxirane and

<1%

phenol, mw <=700

CAS number: 9003-36-5 EC number: 500-006-8

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

## **Natural Calcium Carbonate**

<1%

CAS number: 1317-65-3 EC number: 215-279-6

Classification

Not Classified

## oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

<1%

CAS number: 68609-97-2

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317

#### **ALOCIT 28.15 STANDARD GREY RAL7004**

Trimethylolpropane <1%

CAS number: 77-99-6 EC number: 201-074-9

Classification Repr. 2 - H361fd

1-METHOXY-2-PROPANOL <1%

CAS number: 107-98-2 EC number: 203-539-1

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

Solvent naphtha (petroleum), light arom.

CAS number: 64742-95-6 EC number: 918-668-5

Classification

Muta. 1B - H340 Carc. 1B - H350 Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

Composition comments This mixture contains ≥ 1% Titanium Dioxide (CAS 13463-67-7) The Annex VI classification of

Titanium Dioxide does not apply to this mixture according to its Note 10.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation** Move affected person to fresh air at once. If breathing stops, provide artificial respiration.

When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention

immediately.

**Ingestion** Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not

induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get

medical attention immediately.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water. Get medical attention if any discomfort

continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes and get medical attention. Get medical attention promptly if symptoms occur after

washing.

4.2. Most important symptoms and effects, both acute and delayed

InhalationNo specific symptoms known.IngestionNo specific symptoms known.

**Skin contact** Prolonged skin contact may cause redness and irritation.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient.

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Water. Foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing

media

Not known.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards Fire or high temperatures create: Toxic gases/vapours/fumes of: Carbon dioxide (CO2).

Carbon monoxide (CO). Thermal decomposition or combustion products may include the

following substances: Toxic gases or vapours.

Hazardous combustion

products

Carbon dioxide (CO2). Carbon monoxide (CO). Halogenated hydrocarbons.

#### 5.3. Advice for firefighters

Protective actions during

firefighting

Isolate area. Very toxic to aquatic organisms. Control run-off water by containing and keeping

it out of sewers and watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing. Use air-supplied respirator, gloves and protective goggles.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Keep unnecessary and unprotected personnel from

entering the area. Avoid inhalation of vapours. Isolate area.

## 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste

disposal, see Section 13.

## 6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11

for additional information on health hazards. Collect and dispose of spillage as indicated in

Section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Usage precautions Do not eat, drink or smoke when using this product. Persons susceptible to allergic reactions

should not handle this product. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Store in tightly-closed, original container. Wear suitable protective clothing as

protection against splashing or contamination.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### **ALOCIT 28.15 STANDARD GREY RAL7004**

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Chemical storage.

7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure controls/Personal protection

## 8.1. Control parameters

#### Occupational exposure limits

#### **BARIUM SULPHATE**

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

#### TITANIUM DIOXIDE

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m3, 8 h EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m3, 8 h

#### **Natural Calcium Carbonate**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

#### 1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³ Sk

## Solvent naphtha (petroleum), light arom.

Long-term exposure limit (8-hour TWA): SUP 25 ppm 100 mg/m³ Short-term exposure limit (15-minute): SUP No std. No std.

WEL = Workplace Exposure Limit. Sk = Can be absorbed through skin.

## reaction product: bisphenol-A-(epichlorhydrin) (CAS: 25068-38-6)

**DNEL** Industry - Dermal; Short term systemic effects: 8.3 mg/kg/day

Industry - Inhalation; Short term systemic effects: 12.3 mg/m³ Industry - Dermal; Long term systemic effects: 8.3 mg/kg/day Industry - Inhalation; Long term systemic effects: 12.3 mg/m³ Consumer - Dermal; Short term systemic effects: 3.6 mg/kg/day Consumer - Inhalation; Short term systemic effects: 0.75 mg/m³ Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day Consumer - Dermal; Long term systemic effects: 3.6 mg/kg/day Consumer - Inhalation; Long term systemic effects: 0.75 mg/m³

PNEC - Fresh water; 3 mg/l

- marine water; 0.3 mg/l

Sediment (Freshwater); 0.5 mg/kg
Sediment (Marinewater); 0.5 mg/kg
Intermittent release; 0.013 mg/l

BARIUM SULPHATE (CAS: 7727-43-7)

## **ALOCIT 28.15 STANDARD GREY RAL7004**

**DNEL** Workers - Inhalation; Long term systemic effects: 10 mg/m³

Workers - Inhalation; Long term local effects: 10 mg/m³ Consumer - Inhalation; Long term systemic effects: 10 mg/m³ Consumer - Oral; Long term systemic effects: 13000 mg/kg

PNEC Fresh water; 115 μg/l

STP; 62.2 mg/l

Sediment (Freshwater); 600.4 mg/kg

Soil; 207.7 mg/kg

#### TITANIUM DIOXIDE (CAS: 13463-67-7)

**DNEL** Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

Professional - Inhalation; Long term local effects: 10 mg/m³ Consumer - Oral; Long term systemic effects: 700 mg/kg/day

PNEC marine water; 0.0184 mg/l

Fresh water; 0.184 mg/l Intermittent release; 0.193 mg/l

STP; 100 mg/l

Sediment, marine water; 100 mg/kg Sediment, Fresh water; 1000 mg/kg

Soil; 100 mg/kg

#### C.I. PIGMENT BLACK 11 (CAS: 1317-61-9)

**Ingredient comments** No exposure limits known for ingredient(s).

**DNEL** Workers - Inhalation; Long term systemic effects: 10 mg/m³

Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

## bis-[4-(2,3-epoxipropoxi)phenyl]propane (CAS: 1675-54-3)

**DNEL** Workers - Dermal; Short term systemic effects: 8.3 mg/kg, bw/day

Workers - Inhalation; Short term systemic effects: 12.3 mg/m³ Workers - Dermal; Long term systemic effects: 8.3 mg/kg, bw/day Workers - Inhalation; Long term systemic effects: 12.3 mg/m³

General population - Dermal; Short term systemic effects: 3.6 mg/kg, bw/day General population - Inhalation; Short term systemic effects: 0.75 mg/m³ General population - Oral; Short term systemic effects: 0.75 mg/kg, bw/day General population - Dermal; Long term systemic effects: 3.6 mg/kg, bw/day General population - Inhalation; Long term systemic effects: 0.75 mg/m³

General population - Oral; Long term systemic effects: 0.75 mg/kg, bw/day

PNEC Fresh water; 3 μg/l

marine water; 0.3 µg/l

STP; 10 mg/l

Sediment (Freshwater); 0.5 mg/kg Sediment (Marinewater); 0.5 mg/kg

Sediment; 0.05 mg/kg

Intermittent release; 0.013 mg/l

## BENTONE SD3 (CAS: 121888-67-3)

**Ingredient comments** No exposure limits known for ingredient(s).

## Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700 (CAS: 9003-36-5)

**DNEL** Industry - Dermal; Short term local effects: 8.3 ppm

Industry - Dermal; Long term systemic effects: 104.15 mg/kg/day Industry - Inhalation; Long term systemic effects: 29.39 mg/m³ Consumer - Dermal; Long term systemic effects: 62.5 mg/kg/day Consumer - Inhalation; Long term systemic effects: 8.7 mg/m³ Consumer - Oral; Long term systemic effects: 6.25 mg/kg/day

PNEC - Fresh water; 0.003 mg/l

- marine water; 0.0003 mg/l

Sediment (Freshwater); 0.294 mg/kgSediment (Marinewater); 0.0294 mg/kg

- Soil; 0.237 mg/kg

- Intermittent release; 0.0254

## oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (CAS: 68609-97-2)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.6 mg/m³

Workers - Dermal; Long term systemic effects: 1 mg/kg/day

General population - Inhalation; Long term systemic effects: 0.87 mg/m³ General population - Dermal; Long term systemic effects: 0.5 mg/kg/day General population - Oral; Long term systemic effects: 0.5 mg/kg/day

PNEC Fresh water; 0.106 mg/l

Fresh water, Intermittent release; 0.072 mg/l

marine water; 0.011 mg/l

STP; 10 mg/l

Sediment (Freshwater), dw; 307.16 mg/kg Sediment (Marinewater), dw; 30.72 mg/kg

Soil, dw; 1.234 mg/kg

#### Trimethylolpropane (CAS: 77-99-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.3 mg/m³

Workers - Dermal; Long term systemic effects: 0.94 mg/kg Consumer - Inhalation; Long term systemic effects: 0.58 mg/m³ Consumer - Dermal; Long term systemic effects: 0.34 mg/kg Consumer - Oral; Long term systemic effects: 0.34 mg/kg

## 1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Ingredient comments WEL = Workplace Exposure Limits

**DNEL** Industry - Inhalation; Short term : 553.5 mg/m³

Industry - Inhalation; Long term : 369 mg/m³ Industry - Dermal; Long term : 50.6 mg/m³ Consumer - Inhalation; Long term : 43.9 mg/m³ Consumer - Dermal; Long term : 18.1 mg/m³ Consumer - Oral; Long term : 3.3 mg/m³

PNEC - Fresh water; 10 mg/l

Sediment; 41.6 mg/kgSoil; 2.47 mg/kgSTP; 100 mg/l

## Solvent naphtha (petroleum), light arom. (CAS: 64742-95-6)

**DNEL** Industry - Dermal; Long term systemic effects: 25 mg/kg/day

Industry - Inhalation; Long term systemic effects: 150 mg/m³ Consumer - Inhalation; Long term systemic effects: 32 mg/m³ Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Oral; Long term systemic effects: 11 mg/kg/day

#### 8.2. Exposure controls

#### Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

**Eye/face protection** The following protection should be worn: Chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin

contact is possible.

Other skin and body

protection

AVOID ALL SKIN AND RESPIRATORY CONTACT! Wear appropriate clothing to prevent any

possibility of skin contact. Wear apron or protective clothing in case of contact.

**Hygiene measures** Provide eyewash station. Wash at the end of each work shift and before eating, smoking and

using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing

that becomes contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Check that the

respirator fits tightly and the filter is changed regularly.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to

reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance Coloured paste. or Liquid.

Colour Variable
Odour Slight.

Odour threshold No information available.

**pH** No information available.

Melting point Not determined.

**Initial boiling point and range** Not determined.

Flash point >1500°C

**Evaporation rate** Not determined.

**Evaporation factor** No information available.

## **ALOCIT 28.15 STANDARD GREY RAL7004**

Flammability (solid, gas) No information available.

Upper/lower flammability or

explosive limits

**Bulk density** 

Not determined.

No information available.

Other flammability No information available.

Vapour pressure Not determined. Vapour density Not determined.

Relative density No information available.

Solubility(ies) No information available.

Partition coefficient No information available.

No information available. Auto-ignition temperature

**Decomposition Temperature** No information available.

Not determined. Viscosity

**Explosive properties** No information available.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not available.

9.2. Other information

Other information No information required.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability No particular stability concerns.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Hazardous reactions or instabillity may occur under certain conditions of storage or use.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Thermal decomposition or combustion products may include the following substances: Toxic

products

gases/vapours/fumes of: Carbon dioxide (CO2). Carbon monoxide (CO).

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

## **ALOCIT 28.15 STANDARD GREY RAL7004**

**Inhalation** Vapour may irritate respiratory system/lungs.

**Ingestion** Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

**Skin contact** Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritation of eyes and mucous membranes.

Toxicological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 15,000.0

mg/kg)

. . , . . . . .

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 23,032.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 23,032.0

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Not applicable.

Serious eye damage/irritation

Serious eye Causes serious eye irritation.

damage/irritation

Skin sensitisation

Skin sensitisation Irritating to skin. Prolonged skin contact may cause redness and irritation. May

cause sensitisation by skin contact.

Carcinogenicity

Carcinogenicity Not applicable.

Reproductive toxicity

Reproductive toxicity -

Fertility - NOAEL 750 mg/kg/day, Oral, Rat

fertility

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

**STOT - single exposure** Not applicable.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not applicable.

2,3-EPOXYPROPYL O-TOLYL ETHER

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> 2150 mg/kg, Oral, Rat

## **ALOCIT 28.15 STANDARD GREY RAL7004**

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin. Mucous membranes

Serious eye damage/irritation

Serious eye

Not irritating.

damage/irritation

Skin sensitisation
Skin sensitisation

Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro** Suspected of causing genetic defects.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> 11400 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Unlikely to be hazardous by inhalation because of the low vapour pressure of the

product at ambient temperature.

Skin corrosion/irritation

**Skin corrosion/irritation** Irritating to skin.

Serious eye damage/irritation

Serious eye

Causes eye irritation.

damage/irritation

Respiratory sensitisation

**Respiratory sensitisation** May cause sensitisation or allergic reactions in sensitive individuals.

Skin sensitisation

**Skin sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

Based on available data the classification criteria are not met.

fertility

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

## **ALOCIT 28.15 STANDARD GREY RAL7004**

## Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> >2000 mg/kg, Oral, Rat

Acute toxicity - inhalation

Notes (inhalation LC50) Not applicable.

Specific target organ toxicity - single exposure

**STOT - single exposure** Not available.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Acute toxicity - oral

Acute toxicity oral (LD50

17,100.0

mg/kg)

Species Rat

**ATE oral (mg/kg)** 17,100.0

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC50) Not applicable.

Skin corrosion/irritation

Animal data Moderately irritating.

Serious eye damage/irritation

Serious eye Causes serious eye irritation.

damage/irritation

Skin sensitisation

**Skin sensitisation** Severe skin irritation.

Trimethylolpropane

Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 14,700.0

mg/kg)

Species Rat

**ATE oral (mg/kg)** 14,700.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 10,000.0

mg/kg)

Species Rabbit

**ATE dermal (mg/kg)** 10,000.0

Reproductive toxicity

## **ALOCIT 28.15 STANDARD GREY RAL7004**

Reproductive toxicity -

fertility

Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

**Ecotoxicity** Dangerous for the environment. May cause long-term adverse effects in the aquatic

Ecological information on ingredients.

2,3-EPOXYPROPYL O-TOLYL ETHER

**Ecotoxicity** The product contains a substance which is toxic to aquatic organisms.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

**Ecotoxicity** Toxic to aquatic life.

12.1. Toxicity

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Acute aquatic toxicity

Acute toxicity - fish EC₅o, 96 hours: 3.6 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 1.8 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 11 mg/l, Scenedesmus subspicatus

Chronic aquatic toxicity

Chronic toxicity - fish early Not available.

life stage

Chronic toxicity - aquatic

invertebrates

Not available.

2,3-EPOXYPROPYL O-TOLYL ETHER

**Toxicity** Toxic to aquatic life. Fish

Acute aquatic toxicity

Acute toxicity - fish EC₅o, 96 hours: 2.8 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 3.3 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 5.1 mg/l, Selenastrum capricornutum

bis-[4-(2,3-epoxipropoxi)phenyl]propane

WGK 2 **Toxicity** 

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 1.3 mg/l, Fish

## **ALOCIT 28.15 STANDARD GREY RAL7004**

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 2.1 mg/l, Ceriodaphnia dubia (water flea)

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 11 mg/l, Algae

#### Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 2.54 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 2.55 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: >1000 mg/l, Algae

## oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: > 1.8 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 7.2 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: ~ 844 mg/l, Freshwater algae

## Trimethylolpropane

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >1,000 mg/l, Alburnus alburnus (bleak)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 13,000 mg/l, Daphnia magna NOEC, 21 days: >1,000 mg/l, Daphnia magna

Acute toxicity - aquatic

EC₀, 48 hours: >102 mg/l, Daphnia magna

plants

EC<sub>50</sub>, 72 days: >1,000 mg/l, Pseudokirchneriella subcapitata

## 12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

#### Ecological information on ingredients.

#### reaction product: bisphenol-A-(epichlorhydrin)

Persistence and degradability

Not readily biodegradable.

#### 2,3-EPOXYPROPYL O-TOLYL ETHER

Persistence and degradability

No information available.

## bis-[4-(2,3-epoxipropoxi)phenyl]propane

**Biodegradation** Not readily biodegradable.

## **ALOCIT 28.15 STANDARD GREY RAL7004**

## Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

Persistence and degradability

Not readily biodegradable.

Trimethylolpropane

**Biodegradation** Activated sludge - Degradation 100%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 3.242

2,3-EPOXYPROPYL O-TOLYL ETHER

**Bioaccumulative potential** Not expected to be readily biodegradable.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Bioaccumulative potential log Pow: 2.65 - 3.78, BCF: 3 - 31 31.00,

Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

Bioaccumulative potential log Pow: 3.3, BCF: 150 150.00,

Trimethylolpropane

Bioaccumulative potential BCF: < 17, Cyprinus carpio (Common carp)

Partition coefficient log Pow: -0.47 (26°C)

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Mobility
No data available.

Surface tension
60 mN/m @ 20°C

2,3-EPOXYPROPYL O-TOLYL ETHER

**Mobility** No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

#### **ALOCIT 28.15 STANDARD GREY RAL7004**

#### Ecological information on ingredients.

#### reaction product: bisphenol-A-(epichlorhydrin)

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

12.6. Other adverse effects

Other adverse effects Not known.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Other adverse effects None known.

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff

entering drains, sewers or watercourses.

Waste class EWC NUMBER : Allocation of a waste code number in accordance with the European Waste

Catalogue, should be carried out in agreement with an EA authorised waste disposal

company.

#### SECTION 14: Transport information

Road transport notes SP375 – These substances when carried in Single or Combination packaging's containing a

net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any provisions of ADR provided

the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8

Sea transport notes Chapter 2.10 – 2.10.2.7 – Marine Pollutants packaged in Single or Combination packaging's

containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of this code relevant to Marine Pollutants, provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of Marine Pollutants also meeting the Criteria for inclusion in another class, all provisions of this code relevant to

any additional hazards continue to apply

Air transport notes A197 - These substances when carried in Single or Combination packaging's containing a net

Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of these regulations provided the packaging's meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and

5.0.2.8

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A)

(ADR/RID)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A)

## 14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ICAO class/division 9

## Transport labels



## 14.4. Packing group

ADR/RID packing group III

IMDG packing group

ICAO packing group

## 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

## **ALOCIT 28.15 STANDARD GREY RAL7004**

## **EU legislation** Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No

1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning

the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH),

establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as

Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and

1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Guidance A guide to local exhaust ventilation (LEV) HSG258 (as ammended)

Workplace Exposure Limits EH40.

#### 15.2. Chemical safety assessment

Not applicable.

## SECTION 16: Other information

Revision date 12/11/2021

Revision 15

Supersedes date 30/09/2020

Hazard statements in full H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

The information contained within this document is presented in good faith and is believed to be correct. Alocit International Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.